



70Mpa Max working pressure and the accuracy keep within $\pm 3\%$

All together 10 models with the range from 112N.m to 72000N.m,
which covers the most comprehensive available in the market.

The 360*180 degree swivel is free to operation with no space limitation.

The square drive operate with the high intense socket and suitable with large range
of bolts.

360 degree adjustable reaction arm allows placing in any support point.

Compact design with the raw mterial of advanced aluminum-titanium alloy,high
intense.

The new locking coupler ensures the oil keep free access.

Application:Furniture manufacturing and assemblyCosmetics and daily products
productionPublic utilities and government agencies

Sample:Contact us for free samples

Model	07-S BT	1-SB T	3-SB T	5-SB T	8-SBT	10-SB T	15-SB T	20-SB T	25-SB T	35-SB T	50-SBT
Torque (N.m)	112-1 120	183-1 837	451-4 512	752-7 528	1078-1 0780	1551-1 5516	2063-2 0627	2666-2 6664	3472-3 4725	4866-4 8666	7200-72 000
Bolt size(M)	14-30	16-36	22-48	27-56	30-64	36-72	39-80	42-90	48-100	64-120	72-125
Weight (Kg)	1.8	2	4	7	9.1	13.1	21	25	31	45	87
L1	110.8	133.5	169	202.5	216	237.5	285	299.5	313	361.5	400
L2	139.3	185.5	242	271	309	340.5	395	466.5	461	496.5	516
H1	42	50	68	80	90	100	110	120	137	153	160
H2	65.8	72	95	123	134	142	178	183	200	216	223
H3	76.2	95.5	127	149	167	182	200	220	247	282	291
H4	108.1	131	176.5	199	216.5	231.5	250	269.5	296.5	331.5	341
R1	20.5	26	34	39	47	51	55	59	66	77	81
R2	68.3	99	134	137	171	174	222	250.5	250.5	271	259
Square drive	3/4"	3/4"	1"	1-1/2"	1-1/2"	1-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"

Ningbo Saivs Machinery Co., Ltd

Website: www.saivstool.com www.saivs-industrial.com

Phone& Whatsapp:+8613905748980 Email: seo1@saivs.com