

## SFW-A Pneumatic Torque Wrench

Model	Drive square	Torque	Wspeed	Weight	Dimensions				Noise
		(Nm)	(Rpm)	(Kg)	A	B	C	D	(db)
SFW5A	0.75"	150-500	35	3.7	205	63	69	199	80
SFW8A	0.75"	240-800	18	4.7	247	69	69	199	80
SFW14A	0.75"/1"	405-1350	12	4.7	247	69	69	199	80
SFW20A	1"	600-2000	10	6.6	256	76	85	223	80
SFW28A	1"	840-2800	7	7	270	78	85	223	80
SFW35A	1"/1.5"	1050-3500	6	7.6	283	82	85	223	80
SFW45A	1"/1.5"	1350-4500	4	10.2	306	88	102	265	85
SFW60A	1.5"	1800-6000	2.5	11.7	308	93	102	265	85
SFW80A	1.5"	2400-8000	2.2	13.2	308	102	102	265	85
SFW100A	1.5"/2"	3000-10000	1.4	19.4	390	114	114	271	85
SFW120A	1.5"/2"	3600-12000	1.2	19.4	390	114	114	271	85

SFW-A Pneumatic Torque Wrench

No-Load Speed: 18-2.2Rpm

Customized support: OEM, ODM, OBM

Minimum Torque: 240Nm

Maximum Torque: 8000Nm

Accuracy:  $\pm 5\%$

Square Drive Size: 3/4" inch-1 1/2"

Weight: 4.7 - 13.2 kg

1. Extremely excellent power to weight ratio Wider torque range, suitable for multiple stations
2. The use of multi pole gearbox has no competitive reliability Constant speed and stable output
3. Gun design, in line with human mechanics, more portable
4. Torque output in forward and reverse directions
5. Low noise, non impact output torque
6. Accuracy  $\pm 5\%$  (correct air supply pressure and volume are required)

