

## SMD系列手动扭矩扳手

型号	预置范围 N. m	分度值 N. m	总长 mm	有效力臂 mm	质量 kg	方榫公称尺寸
SMD-5	1-5	0.05	186	120	0.20	6.3mm (1/4" )
SMD-10	2-10	0.1	203	140	0.25	10mm (3/8" )
SMD-22.5	5-22.5	0.25	257	190	0.45	10mm (3/8" )
SMD-25细	5-25	0.25	225	165	0.28	10mm (3/8" )
SMD-25粗	5-25	0.25	257	190	0.45	10mm (3/8" )
SMD-30	5-30	0.25	255	190	0.45	10mm (3/8" )
SMD-50	10-50	0.5	307	240	0.55	10mm (3/8" )
SMD-60	10-60	0.5	307	240	0.55	10mm (3/8" )
SMD-100	20-100	1	420	350	0.90	12.5mm (1/2" )
SMD-180	40-180	1	525	430	1.50	12.5mm (1/2" )
SMD-200	40-200	1	525	430	1.50	12.5mm (1/2" )
SMD-230	50-230	1	525	430	1.50	12.5mm (1/2" )
SMD-300	60-300	1.5	680	575	2.85	12.5mm (1/2" )
SMD-360	60-360	2	680	655	3.15	20mm (3/4" )
SMD-400	100-400	2	780	655	3.15	20mm (3/4" )
SMD-450	100-450	2.5	890	755	3.50	20mm (3/4" )
SMD-500	100-500	2.5	890	755	3.50	20mm (3/4" )
SMD-600	150-600	3	890	755	3.50	20mm (3/4" )
SMD-680	200-680	4	1098	990	6.50	20mm (3/4" )
SMD-760	200-760	4	1098	990	6.50	20mm (3/4" )
SMD-800	200-800	4	1098	990	6.50	20mm (3/4" )
SMD-1000	200-1000	5	1295	1180	7.80	25mm (1" )
SMD-1200	400-1200	5	1300	1180	8.00	25mm (1" )
SMD-1500	450-1500	7	1300	1180	8.50	25mm (1" )
SMD-2000	720-2000	16	1300	1180	8.50	25mm (1" )
SMD-2500	900-2500	20	1400	1200	14.45	25mm (1" )
SMD-3000	1000-3000	30	1400	1200	14.80	25mm (1" )
SMD-4000	1600-4000	30	1500	1368	25.00	38mm (1-1/2" )
SMD-5000	2200-5000	40	1605	1475	26.50	38mm (1-1/2" )
SMD-6000	2800-6000	40	1605	1475	26.50	38mm (1-1/2" )













Grey	Blue	Blue	Blue	Blue	Blue
		Blue	Blue	Blue	Blue
Grey	White	White	White	White	White
Grey	Yellow	Yellow	Yellow	Yellow	Yellow
Grey	White	White	White	White	White
Grey	Yellow	Yellow	Yellow	Yellow	Yellow
Grey	White	White	White	White	White
Grey	Yellow	Yellow	Yellow	Yellow	Yellow
Grey	White	White	White	White	White

---

Grey	Blue	Blue	Blue	Blue	Blue
		Blue	Blue	Blue	Blue
Grey	White	White	White	White	White
Grey	Yellow	Yellow	Yellow	Yellow	Yellow
Grey	White	White	White	White	White
Grey	Yellow	Yellow	Yellow	Yellow	Yellow



--	--	--	--	--	--






--	--	--	--

--	--	--	--

















## SMD Series Manual Torque Wrench

Model	Torque Range (Nm)	Division Value (Nm)	Total Length (mm)	Effective Force Arm (mm)	Weight (kg)	Square Size
SMD-5	1-5	0.05	186	120	0.20	6.3mm (1/4" )
SMD-10	2-10	0.1	203	140	0.25	10mm (3/8" )
SMD-22.5	5-22.5	0.25	257	190	0.45	10mm (3/8" )
SMD-25	5-25	0.25	225	165	0.28	10mm (3/8" )
SMD-25	5-25	0.25	257	190	0.45	10mm (3/8" )
SMD-30	5-30	0.25	255	190	0.45	10mm (3/8" )
SMD-50	10-50	0.5	307	240	0.55	10mm (3/8" )
SMD-60	10-60	0.5	307	240	0.55	10mm (3/8" )
SMD-100	20-100	1	420	350	0.90	12.5mm (1/2" )
SMD-180	40-180	1	525	430	1.50	12.5mm (1/2" )
SMD-200	40-200	1	525	430	1.50	12.5mm (1/2" )
SMD-230	50-230	1	525	430	1.50	12.5mm (1/2" )
SMD-300	60-300	1.5	680	575	2.85	12.5mm (1/2" )
SMD-360	60-360	2	680	655	3.15	20mm (3/4" )
SMD-400	100-400	2	780	655	3.15	20mm (3/4" )
SMD-450	100-450	2.5	890	755	3.50	20mm (3/4" )
SMD-500	100-500	2.5	890	755	3.50	20mm (3/4" )
SMD-600	150-600	3	890	755	3.50	20mm (3/4" )
SMD-680	200-680	4	1098	990	6.50	20mm (3/4" )
SMD-760	200-760	4	1098	990	6.50	20mm (3/4" )
SMD-800	200-800	4	1098	990	6.50	20mm (3/4" )
SMD-1000	200-1000	5	1295	1180	7.80	25mm (1" )
SMD-1200	400-1200	5	1300	1180	8.00	25mm (1" )
SMD-1500	450-1500	7	1300	1180	8.50	25mm (1" )
SMD-2000	720-2000	16	1300	1180	8.50	25mm (1" )
SMD-2500	900-2500	20	1400	1200	14.45	25mm (1" )
SMD-3000	1000-3000	30	1400	1200	14.80	25mm (1" )
SMD-4000	1600-4000	30	1500	1368	25.00	38mm (1-1/2" )
SMD-5000	2200-5000	40	1605	1475	26.50	38mm (1-1/2" )
SMD-6000	2800-6000	40	1605	1475	26.50	38mm (1-1/2" )



