



Repeatability +/- 3%

700 bar/10000psi maximum operation pressure

5 different models from 230 Nm to 45,000 Nm

Designed for tighten and loosen high torque applications

360° x 180° uni swivel quick release couplings

Maximum torque power with minimum wall thickness

Various cassettes, adaptors and reducers are available

Durable structure, aluminium-titanium alloy and light body

Suitable for continuous operations at maximum pressure

Pressure relief valve prevents over pressure

Application: Water and energy industries
Food manufacturing and processing
Construction and structural assembly

Sample: Contact us for free samples

TYPE	Torque	Nut Sizes	Power Head Weight	Cassette Weight	Sizes					
	N.m	mm	Kg	Kg	L1	L2	H1	H2	W1	W2
2 SOW	232 ~ 2328	19 ~ 55	1	1.6	195.4	186	125.9	102.3	32	51
	241 ~ 2414	60	1	1.7	195.4	186	128.5	105	32	51
4 SOW	585 ~ 2510	34 ~ 36								
	585 ~ 5021	41	2	4.4	261.6	245	177	135.7	42	66
	585 ~ 5858	46 ~ 65	2	4.6	261.6	245	187	145.7	42	66
	647 ~ 6474	70 ~ 80								
8 SOW	1094 ~ 10941	41 ~ 95	3.3	8	304	300	207	169	53	83
	1177 ~ 11774	100 ~ 105	3.3	8.4	304	300	216	178	53	83
14 SOW	1852 ~ 18521	50 ~ 117	5.5	11.6	361	361	239	204	64	99
30 SOW	4188 ~ 41882	110 ~ 155	11.4	29	441	430	303	272	85	131
	4459 ~ 44593	160 ~ 175	11.4	30	441	430	315	285	85	131

Ningbo Saivs Machinery Co., Ltd

Website: www.saivstool.com www.saivs-industrial.com

Phone& Whatsapp:+8613905748980 Email: seo1@saivs.com

2SOW				4SOW				8SOW				14SOW				30SOW			
Type	R	A	MaxTorque	Type	R	A	MaxTorque	Type	R	A	MaxTorque	Type	R	A	MaxTorque	Type	R	A	MaxTorque
2SOW-19	27	16	2328	4SOW-34	36	16	2510	8SOW-41	46	22	10941	14SOW-50	60	31	18521	30SOW-85	78	28	41882
2SOW-22	27	14	2328	4SOW-36	36	15	2510	8SOW-46	46	19	10941	14SOW-55	60	28	18521	30SOW-90	78	27	41882
2SOW-27	27	11	2328	4SOW-41	39	15	5021	8SOW-50	46	17	10941	14SOW-60	60	25	18521	30SOW-95	83	28	41882
2SOW-30	29	12	2328	4SOW-46	42	15	5858	8SOW-55	50	18	10941	14SOW-65	60	22	18521	30SOW-100	83	25	41882
2SOW-32	29	11	2328	4SOW-50	44	15	5858	8SOW-60	52	17	10941	14SOW-70	60	19	18521	30SOW-105	89	28	41882
2SOW-34	31	11	2328	4SOW-55	46	14	5858	8SOW-65	55	17	10941	14SOW-75	63	19	18521	30SOW-110	89	25	41882
2SOW-36	31	10	2328	4SOW-60	50	15	5858	8SOW-70	58	17	10941	14SOW-80	66	19	18521	30SOW-115	95	28	41882
2SOW-41	34	10	2328	4SOW-65	53	15	5858	8SOW-75	60	17	10941	14SOW-85	69	19	18521	30SOW-117	95	27	41882
2SOW-46	37	10	2328	4SOW-70	56	15	6474	8SOW-80	63	16	10941	14SOW-90	72	20	18521	30SOW-120	95	25	41882
2SOW-50	40	11	2328	4SOW-75	59	15	6474	8SOW-85	66	16	10941	14SOW-95	74	19	18521	30SOW-125	101	29	41882
2SOW-55	43	11	2328	4SOW-80	61	15	6474	8SOW-90	69	17	10941	14SOW-100	77	19	18521	30SOW-130	101	26	41882
2SOW-60	46	11	2414					8SOW-95	71	16	10941	14SOW-105	80	19	18521	30SOW-135	104	26	41882
								8SOW-100	75	17	11774	14SOW-110	83	19	18521	30SOW-140	110	29	41882
								8SOW-105	78	17	11774	14SOW-115	87	20	18521	30SOW-145	110	26	41882
												14SOW-117	87	19	18521	30SOW-150	116	29	41882
																30SOW-155	116	26	41882
																30SOW-160	128	36	44593
																30SOW-165	128	33	44593
																30SOW-170	128	30	44593
																30SOW-175	128	27	44593

Ningbo Saivs Machinery Co., Ltd

Website: www.saivstool.com www.saivs-industrial.com

Phone& Whatsapp:+8613905748980 Email: seo1@saivs.com